

# TELESTO™

## 80/82.5 mm



2 YEAR WARRANTY



CLAMSHELL™



CUTTER



80/82.5 mm

### Key features

- Optimized price/performance ratio versus application
- Leading-edge technologies and quality
- Innovative smart design with a vast choice of colored front covers



CHARACTERISTICS	UNIT	TELESTO™
Printing speed (max)	mm/s	130
Printing width	mm	72/80
2 color print capability	---	YES
Resolution	dot/mm	8
Number of dots	dot	576 (80 mm), 640 (82.5 mm)
Number of columns	column	48/36 (80 mm), 53/40 (82.5 mm)
Character size	dot*dot	12*24 or 16*24
Resident code page	---	CP437/858 + user defined
Bar code type	---	Interleaved 2/5, JAN8 (EAN8) & JAN13 (EAN13), Code 39&128, Codabar
Paper width	mm	80/82.5
Paper roll diameter	mm	83
Paper thickness	µm	Up to 80
Paper loading	---	Clamshell™
Operating voltage	VDC	24
Current consumption	A	3
Head pulse life	pulse	1*10 <sup>6</sup>
Mechanical reliability	km	100
Dimensions (W*D*H)	mm	140*187.4*128
Operating temperature	°C/F	5 to 45/41 to 113
Operating humidity	%RH	20 to 85
Cutter	---	Auto cutter (full or partial cuts) and integrated plastic tear bar
Cutter life	cuts	800 000
Data buffer	Kbyte	1
Flash Memory	Kbytes	48
Interface	---	RS232&USB, Bluetooth™ Class 1
Driver	---	Windows™ 98/00/XP - OPOS
Emulation	---	ESC/POS™
CEM & Safety standards	---	CE Class B, FCC Part 15, C-Tick, UL60950, CSA22.2 60950, IEC 60950
Added features	---	Paper low sensor, 1 CDKO, Buzzer, Fixation hole for wall mounting
Accessories	---	Wall mounting kit, Colored front covers (black, cool white, lavender, plum), Extended 2MB flash memory, Powered USB cable