

T2150 Serial Matrix

Fast, reliable class leading printers



The T2150 and T2250 are highly featured, reliable and stylish machines. Performance and workload, ergonomics, maintainability, excellent price - everything has been incorporated to ensure they are the only acceptable choice for the customer.

Continuous and cut forms are fed at the front for quick and easy loading. This ensures a straight path for the forms resulting in reliable paper transportation, even on 6-part stock. Loading paper is easier. The operator does not have to fumble over or around the printer to gain access to rear located tractors. If 'tear at top of form' is inadequate for your application, the 2150S features a cutting device which separates forms automatically

User intervention is kept to a minimum with a suite of features designed to ensure the products run at optimum reliability and performance.

The product is at home in the computer room, data processing room, or in the office. An unobtrusive 52dBA acoustic rating results in a printer, which is half as quiet, compared with many competitive models.

Product Highlights

- Print speeds up to 750 cps
- 26,000 pages per month workload
- 80 columns
- 24 pin print head produces excellent print quality
- Automatic gap adjustment and quick tear
- Straight through paper path for easy forms loading
- Parallel and Serial interfaces standard
- LAN, IBM AS400/iSeries, Mainframe optional

Available Configuration:

- T2150** Standard Product
- T2150S** with Automatic cutter
- LA550N** DEC compatible version

| | |
|------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Print Speed | Draft: 500cps; NLQ: 180cps; LQ: 90cps |
| Resolution | Up to 360 x 360dpi |
| Printhead Life | 400 million characters |
| Standard Connectivity | Parallel (bi-directional) and serial RS232. 64Kb selectable |
| Optional Connectivity | Serial RS422, serial current loop (20mA), Ethernet 10/100 Base T, USB Parallel Adapter, HostCom pocket coax matrix for IBM mainframe HostCom pocket twinax for AS400, iSeries, System 3X |
| Standard Emulation | IBM proprinter XL24, Epson LA2550, Tally MTPL + barcode + LCP |
| Optional Emulation | DEC LA75; MT50 (Diskette and manual program packs) |
| Fonts | HS draft (sans serif), draft (sans serif), Courier, Roman, Sans Serif, Prestige, Script, OCR-A/B*, 19 barcodes and large character printing. Range of Arabic fonts (Arabic model) |
| Consumables | Ribbon: 3.6 million characters |
| STD Paper Handling | Push tractors with paper parking and automatic gap adjustment (AGA). Cut sheet front insertion with AGA |
| Opt'l Paper Handling | Additional push tractor, front. Additional push tractor, rear. Front single bin automatic sheet feeder. Paper cutting device (T2150S only) |
| Paper Type | Continuous forms, Cut sheet |
| Paper Weight | Continuous forms 60-120gsm; Cut sheet 80-120gsm |
| Paper Size | |
| Physical Weight | 9Kg |
| PhysicalSize | (HxWxD): 300x460x295mm |
| Power Voltage | 230V |
| Power Consumption | 40W printing |
| Workload | 26,000 pages per month |
| Drivers | |
| Temperature | +10° to +35°C |
| Humidity | 20% to 80% |
| Acoustic | 53dB(A) |
| Warranty | 1 year return to base |

